

SMART LUBES

Product Data Sheet

Smart lubes SLT 20W-50

Superior sludge protection for greater engine reliability

Description

Smart lubes SLT is one of the world's most trusted motor oils. It provides superior protection against oil burn-off, 60% better than the tough industry test* It is one of the world's leading oils for high mileage cars.

It's more than just oil. It's liquid engineering that protects your higher mileage engine from oil burn-off and extends the life of your engine. As your engine ages, oil burns off faster. Over time, this can cause increased engine wear, shortening the life of your engine. Smart lubes SLT 20W-50 is a unique formulation specifically engineered to meet the changing needs of your high mileage vehicle. Its technology is proven to provide 60% superior oil burn-off protection versus the tough industry standard.

* vs API SL Industry Standards

Application

Smart lubes SLT 20W-50 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SL/CF or earlier specification 20W-50 lubricant.

Advantages

Smart lubes SLT 20W-50 is engineered to extend the life of your engine with:

- 60% Superior oil burn-off protection *
- Additives to minimise compression loss and provide engine protection.
- Formulation that protects seals for longer, helping reduce leakage.
- Protect against wear and harmful deposits.
- Help your vehicle live longer with Smart lubes SLT 20W-50

Typical Characteristics

| Name | Method | Units | Smart lubes SLT 20W-50 |
|---------------------------|------------|-------|------------------------|
| Density @ 20C | ASTM D4052 | g/ml | 0.886 |
| Viscosity, Kinematic 100C | ASTM D445 | mm²/s | 19.1 |
| Viscosity, Kinematic 40C | ASTM D445 | mm²/s | 174.8 |
| Viscosity Index | ASTM D2270 | None | 124 |
| Pour Point | ASTM D97 | °C | -30 |
| Flash Point, PMCC | ASTM D93 | °C | 210 |
| CCS @ 15 | ASTM D5293 | °C | 9300 |

Product Performance Claims

^{*} vs API SL Industry Standards