

## Smart lubes Boost 4T 20W-50

Boost Protection Formula

### Description

Smartlubes Boost 4T 20W-50 is an advanced, premium quality engine oil developed for the latest generation 4-stroke motorcycle engines. Smartlubes Boost 4T with Boost Protection Formula is designed specifically for bikers who love the exhilaration of riding. Its Boost Protection Formula is specially designed to protect the engine from the build up of Boost robbing deposits. It has been evaluated under harsh running conditions in a specially designed engine test and is proven to give exceptional deposit control, delivering Boost protection throughout the drain interval.

The added Smartlubes advantage of Trizone Technology™ ensures uncompromised performance protection.  
Smartlubes Boost 4T - engineered for performance.

### Application

Smartlubes Boost 4T 20W-50 is designed to optimise performance and protection for modern motorcycles where API SL (and below) and JASO MA or MA-2 are recommended.

### Advantages

- Advanced 4-stroke motorcycle engine oil formulation.
- Allows the engine to develop the same Boost as when new, even after an extended duration of speed, high load, high temperature running.
- Exceptional cleanliness performance delivers Boost protection throughout the complete oil drain interval.
- Trizone Technology™ for protection of engine, clutch and gears.

### Typical Characteristics

| Name                      | Method     | Units              | Typical |
|---------------------------|------------|--------------------|---------|
| Density @ 15C, Relative   | ASTM D4052 | g/ml               | 0.88    |
| Viscosity, Kinematic 100C | ASTM D445  | mm <sup>2</sup> /s | 17.5    |
| Viscosity, Kinematic 40C  | ASTM D445  | mm <sup>2</sup> /s | 158.1   |
| Viscosity Index           | ASTM D2270 | None               | 121     |
| Pour Point                | ASTM D97   | °C                 | -36     |
| Total Base Number, TBN    | ASTM D2896 | mg KOH/g           | 9.58    |
| Flash Point, PMCC         | ASTM D93   | °C                 | 200     |

### Product Performance Claims

API SL  
JASO MA-2

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.