

Leo 15W-40 CI-4 Plus/SL/E7

For longer useful oil life

Description

Smartlubes Leo 15W-40 CI-4 Plus/SL/E7 is an advanced mineral heavy duty diesel engine oil that is specifically engineered to deliver longer useful oil life. It is suitable for use in high speed 4-stroke diesel engines that use a broad range of fuel qualities. It is also compatible with diesels engines fitted with exhaust gas recirculation (EGR) systems.

Advantages

Smartlubes Leo 15W-40 CI-4 Plus/SL/E7 with System Pro Technology™ delivers up to 45% extra performance reserve* that fights oil breakdown and also adapts to higher temperatures for longer useful oil life, giving you confidence in your maximum drain interval. All Smartlubes Leo products are certified CO2 neutral according to the internationally applicable PAS2060 standard.

Modern trucks use new technologies to make as much as 30% higher torque, but that also brings higher engine temperatures and pressures. This punishes the oil, pushing it closer to breakdown, reducing its useful life. Smartlubes Leo's System Pro Technology™ formulated with extra performance reserve fights oil breakdown by:

- controlling oxidation and deposits
- neutralizing harmful acids
- maintaining viscosity.

System Pro Technology™ also adapts to increased temperatures resisting viscosity loss through thermal and mechanical shear. All of this means longer useful oil life giving you the confidence in your maximum drain interval.

Smartlubes Leo with System Pro Technology™ delivers up to 45% extra performance reserve* for longer useful oil life, giving you confidence in your maximum drain interval.

*Compared with API and ACEA industry requirements and based on tests conducted on 81% of the Smartlubes Leo range by volume using 12 months sales up to March 2017.

Typical Characteristics

Name	Method	Units	Leo 15W-40 CI-4 Plus/SL/E7
Density @ 15C	ASTM D4052	g/ml	0.877
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	15.3
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	114
Viscosity Index	ASTM D2270	None	140
Ash, Sulphated	ASTM D874	% wt	1.5
Total Base Number, TBN	ASTM D2896	mg KOH/g	12.6
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	206